

End a Transaction

Ends (commits) a transaction.

Path Components

```
POST /lightwave/api/v1/transaction/{transaction-id}
```

Name	Use	Description
transaction-id	required	The transaction ID value returned from a previous begin transaction call.

Parameters

Request

Name	Use	Description
lw-correlation-id	optional	A caller supplied identifier to be copied to the response.
lw-suppress-status	optional	Use to indicate that the HTTP response status code should be "200 OK", regardless of the outcome of the operation.

Response

Name	Description
lw-correlation-id	The value of the correlationId supplied in the request, if any.
lw-error	If an error occurred, a description of the error.
lw-http-reason	The HTTP response reason. Present if lw-suppress-status was supplied in the request.
lw-http-status	The HTTP response status. Present if lw-suppress-status was supplied in the request.
lw-transaction-id	The transaction ID of the TMF transaction associated with the request, if any.
lw-transaction-state	The transaction state of the TMF transaction associated with the request, if any.

Example

Request

```
POST http://lightwave.example.com/lightwave/api/v1/transaction/2c00031c9b890000c40ff4182950cac4 HTTP/1.1  
Content-Length: 0
```

Response

```
HTTP/1.1 200 OK  
Content-Length: 0  
lw-transaction-state: committed  
lw-transaction-id: 2c00031c9b890000c40ff4182950cac4
```