

Abort a Dialog

Aborts an existing dialog. For more information on Pathway Dialog processing refer to *HP NonStop TS/MP Pathsend and Server Programming Manual*.

Path Components

```
DELETE /lightwave/api/v1/dialog/{dialog-id}
```

Name	Use	Description
dialog-id	required	A dialog ID returned from a previous request which had the Begin or Resume Dialog I/O Options selected.

Parameters

Request

Name	Use	Description
lw-correlation-id	optional	A caller supplied identifier to be copied to the response.
lw-suppress-status	optional	Use to indicate that the HTTP response status code should be "200 OK", regardless of the outcome of the operation.
lw-transaction-id	optional	The transaction ID of the transaction in which this request should be enlisted

Response

Name	Description
lw-correlation-id	The value of the correlationId supplied in the request, if any.
lw-dialog-id	The Dialog ID associated with the request.
lw-dialog-state	The current statue of the Dialog.
lw-error	If an error occurred, a description of the error.
lw-http-reason	The HTTP response reason. Present if lw-suppress-status was supplied in the request.
lw-http-status	The HTTP response status. Present if lw-suppress-status was supplied in the request.
lw-transaction-id	The transaction ID of the TMF transaction associated with the request, if any.
lw-transaction-state	The transaction state of the TMF transaction associated with the request, if any.

Example

Request

```
DELETE http://lightwave.example.com/lightwave/api/v1/dialog/0001000000000002 HTTP/1.1
Content-length: 0
```

Response

```
HTTP/1.1 200 OK
Content-Length: 0
lw-dialog-id: 0001000000000002
lw-dialog-state: aborted
```